

Cleaning Tool for Injector Nozzle Seat

KL-1383-119

Suitable for the Common-Rail Diesel engines DW12 on Peugeot, Citroën, Fiat, Lancia 2.2 HDI, 2.2 JTD.

In a single machining operation, the specially shaped cleaning tool produces a clean finish on the injector mounting hole, the nozzle seal seat and the small aperture leading to the combustion chamber.

Indispensable procedure before re-installing an injection nozzle to avoid leakage between cylinder head and injection nozzle.

Technical Data:

Drive:	T-handle
Length:	275 mm
Cleaning tool-Ø:	7.5 / 17 / 19.6 mm



Cleaning Tool for Injector Nozzle Seat

KL-1383-1311

Suitable for the 1.6l PSA Common-Rail Diesel engines on

- Fiat 1.6l HDI; engine code: DV6, 9HX, 9HY, 9HZ
- Ford 1.6l TDCi; engine code: G8DA, G8DB, HHDA, HHJA, HHJB
- Volvo 1.6l D; engine code: D4164T
- Mazda 1.6l D; engine code: Y6

In a single machining operation, the specially shaped cleaning tool produces a clean finish on the injector mounting hole, the nozzle seal seat and the small aperture leading to the combustion chamber.

Indispensable procedure before re-installing an injection nozzle to avoid leakage between cylinder head and injection nozzle.

Technical Data:

Drive:	T-handle
Length:	295 mm
Cleaning tool-Ø	7.5 / 17 / 17.6 / 18.7 mm



Compressed-Air Adaptor for Glow Plug Bore M8x1

KL-1383-118

Universally suitable for Citroën, Fiat, Ford, Lancia, Mercedes, Opel/Vauxhall, Suzuki, Volvo etc. such as Mercedes: OM639, OM640, OM642, OM651; PSA: 2.7 HDI engine: DT17, 3.0 HDI engine: DT20

Screwing in the compressed-air adaptor KL-1383-118 into the glow plug bore and injecting air into the combustion chamber prevent impurities from entering the combustion chamber.

Technical Data:

Thread:	M8x1
Length:	178 mm
Pipe-Ø:	Ø12 x 80 mm



Compressed-Air Adaptor for Glow Plug Bore

KL-0369-55 B

Universally suitable for e.g. BMW, Mercedes, Chrysler, Opel/Vauxhall, Nissan Renault etc.

Screwing the compressed-air adaptor KL-0369-55 B into the glow plug bore and injecting air into the combustion chamber prevents impurities from entering the combustion chamber.

Technical Data:

Thread:	M10x1
Length:	178 mm
Pipe-Ø:	15 x 110 mm



Compressed-Air Adaptor for Glow Plug Bore M10x1.25

KL-0186-1631

Universally suitable, for example for Toyota, Lexus etc.

Screwing in the compressed-air adaptor KL-0186-1631 into the glow plug bore and injecting air into the combustion chamber, prevents impurities from entering the combustion chamber.

Technical data

Thread:	M10x1.25
Length:	207 mm
Pipe-Ø:	15 mm

