

KL-4064-601 K Screwdriver Bit Insert Set (5-point), 1/4"



1/4"

Suitable e.g. for:

- Mass Air Flow Sensor VW-Audi, Mercedes.
- Mercedes outside mirror.
- Immobiliser control unit (EWS3) on Rover 75 and MG ZT.
- Pumps in pump-line-injection systems on Mercedes commercial vehicles (e.g. Atego, Actros).

9 Screwdriver Bit Inserts in a plastic storage case.

For loosening and tightening the new 5 point tamper-proof bolts.

Consists of:

9x Bit-Insert, Drive: hex 1/4"

1x Bit-Holder (for retaining screwdriver bit inserts) hex 1/4"; Drive square 1/4"

1x Plastic storage case



Technical Data:

| | |
|----------------------|------------------------------------|
| Size: | 10, 15, 20, 25, 27, 30, 40, 45, 50 |
| Drive (Bit-Insert): | hex 1/4" |
| Drive (Bit-Holder): | 1/4" |
| Length (Bit-Insert): | 25 mm |
| Weight: | 100 g |

KL-4064-602 K Screwdriver Bit Insert Set (5-point) with ratchet in a storage case



1/4"



For loosening and tightening the 5-point tamper-proof screws with bore.

Screwdriver Bit Inserts (9 pieces):

1/4" hex Drive; size 10, 15, 20, 25, 27, 30, 40, 45, 50

Bit-reversible ratchet:

hex 1/4"; fine toothed, left-/right reversible

Plastic storage case

Technical Data:

| | |
|--------------------------------------|------------------------------------|
| Size: | 10, 15, 20, 25, 27, 30, 40, 45, 50 |
| Drive (Bit-Insert): | SK 1/4" |
| Drive (Bit-Holder): | SK 1/4" |
| Length (Bit-Insert): | 25 mm |
| Length (ratchet): | 94 mm |
| Overall height (ratchet), incl. bit: | 28 mm |
| Weight: | 140 g |

6

KL-0369-10 Injector Socket (width across flats 22 mm hex)



1/2"

Suitable for diesel engines from : VW-Audi, BMW, Ford, Opel/Vauxhall, Rover, Mercedes, Seat, Volvo, etc.

Special cut-out hex socket for removing and installing diesel injectors without damage to fuel return lines.


Technical Data:

| | |
|--------|-------|
| Size: | 22 mm |
| Drive: | 1/2" |

KL-0511-1 Injector Socket (width across flats 27 mm bi-hex)



1/2"



Suitable for: BMW (e.g. M21, M41, M51) as well as Ford, VW and Mercedes diesel engines.

Special cut-out hex socket for removing and installing diesel injectors without damage to fuel return lines.


Technical Data:

| | |
|--------|-------|
| Size: | 27 mm |
| Drive: | 1/2" |

KL-0511-2 Injector Socket (28 mm, bi-hex)



1/2"



Suitable for: Alfa Romeo; Chrysler; Rover; MAN 2.5 TD

Special cut-out hex socket for removing and installing diesel injectors without damage to fuel return lines.

Technical Data:

| | |
|------------------|-------|
| Size (bi-hex)::: | 28 mm |
| Drive | 1/2" |